
PRESSURE TRANSMITTER

Models 148 / 248 / 348



FEATURES

- Resistant to pressure spikes
- High accuracy (≤0.15%)
- Response time less than 1 mSec
- Welded stainless steel construction
- All welded NEMA 4X design
- 3X overpressure rating
- mV/V, 0-5 Vdc, 4 to 20 mA outputs

TYPICAL APPLICATIONS

- Die casting
- Stamping presses
- Rolling mills
- Injection molding
- Compressors and pumps
- Off road vehicles
- Hydraulic usage
- Test stands

DESIGNED FOR HARSH CONDITIONS

All welded stainless steel construction combined with sensors that are hermetically sealed with no adjustment controls provide an airtight and watertight transducer preventing contamination from the application environment.

SPIKE RESISTANT

The “48” Series is made to withstand overloads and severe pressure spikes that can offset, weaken or destroy other sensors. The minimum 3X overpressure rating on the X48 means better than 0.15% accuracy while still offering a response time of less than a millisecond. It’s designed to provide years of reliable, repeatable service.

FLEXIBLE TO MEET YOUR NEEDS

Standard pressure ranges are from 3 PSI thru 15K PSI (0.2 to 1034 bar) with outputs of mV/V, 0-5 Vdc and 4-20 mA. Additional outputs are also available. Viatran’s available standard options and ability to modify products provide flexibility to meet your specified application needs.

Standard options include alternate pressure ports, electrical connectors, multiple pressure formats and various electrical outputs. Viatran’s rugged reputation is also standard.

MECO MEASUREMENTS & CONTROLS
Via Paolo Uccello, 4 20148 Milano
Tel. +39 02 4 692 680 Fax +39 02 4 694 602 info@mecoitalia.it www.mecoitalia.it

Models 148 / 248 / 348

PERFORMANCE

Full Scale Pressure Range .....0-15 thru 0-200 PSIA (0-1.0 thru 0-13.7 bar)
.....0-3 thru 0-15K PSIG, PSIS (0-0.2 thru 0-1034 bar)
.....0-15 PSIV*

Accuracy (combined linearity, hysteresis & repeatability)
0-200 PSI (0-13.7 bar) .....≤0.25%
300-15K PSI (20-1034 bar) .....≤0.15%
Zero Balance .....≤±1% FSO

Full Scale Output (FSO)
148 .....mV/V output, range dependent
248 .....5 Vdc ±1%
348 .....16 mA ±1%

Resolution .....Infinite
Long-Term Stability .....≤0.5% FSO per 6 months
Compensated Temperature Range .....70°F to 170°F (21°C to 76°C)
Operating Temperature.....-40°F to 185°F (-40°C to 85°C)
Storage Temperature Limits.....-65°F to 250°F (-54°C to 121°C)
Temperature Effect on Zero .....≤±1% FSO per 100°F
Temperature Effect on Span .....≤±1% FSO per 100°F

ELECTRICAL

Supply Voltage
148 .....10Vdc nominal, 15V max
248 .....9 to 30 Vdc
348 .....9 to 30 Vdc
Power Supply Regulation Effect .....≤±0.05% FSO per volt over the supply voltage range (248/348 only)

Output Signal
148 .....2.5 to 10 mV/V
248 .....0 - 5 Vdc
348 .....4 - 20 mA

Circuit Protection .....Reverse polarity protected
Insulation Resistance .....<5nS conductance
Response Time .....≤1 mSec for 10% to 90% FSO
Electrical Connection.....6 pin hermetic, bayonet-style, 303 SST weldmount connector

	148	248	348
Pin A	+Power	+Power	+Power/Signal
Pin B	-Power	-Power	-Power/Signal
Pin C	+Signal	+Signal	No connection
Pin D	-Signal	-Signal	No connection
Pin E	No connection	No connection	No connection
Pin F	No connection	No connection	No connection

MECHANICAL

Pressure Connection.....1/4" NPT female
Proof Pressure .....3 times FSPR or 20K PSI (1378 bar), whichever is less
148 ≥ 300 PSI (20 bar).....1.5 times FSPR or 20K PSI (1378 bar), whichever is less
Burst Pressure.....5 times FSPR or 45K PSI (3102 bar), whichever is less
Pressure Cavity Volume.....3 mL without fittings

MATERIALS OF CONSTRUCTION

Wetted Parts
0-3 thru 200 PSI (0-0.2 thru 13 bar) .....316 stainless steel
>200 PSI (>13 bar).....15-5PH stainless steel
Housing .....316/304 stainless steel
Weight .....10 oz
Mounting.....May be supported by process piping
Identification.....Laser etched onto body

ACCESSORIES

Digital indicators
Mounting bracket
Mounting electrical connector/assembly
Protective cover

* For PSIV and Compound Range units:

Temperature Effect on Zero .....≤±3.0% per 100°F
Compensated Temperature Range .....32°F to 170°F (0°C to 77°C)
148 output signal .....5 mv/V


MECO MEASUREMENTS & CONTROLS
Via Paolo Uccello, 4 20148 Milano
Tel. +39 02 4 692 680 Fax +39 02 4 694 602 info@mecoitalia.it www.mecoitalia.it
Viatran A Dynisco Company

OPTIONS

Electrical Connection	BH	C21-10-6PN-20-0P1
	BI	CF3102E-14S-2P
	BZ	Micro change
	ZU	Direct coupled cable
	ZY	1/2" (M) NPT conduit connection
Alternate Pressure Ports	WG	G-1/4" (F)
	YC	MS33656-04 (M)
	YD	MS33656-06 (M)
	YG	MS16142-04 (F)
	YK	1/4" NPT (M)
	YU	MS16142-06 (F)
Performance Options	DE	Internal calibration
	DG	Improved temperature compensation
	DH	Special ranging
	DM	Modified full scale output
	DQ	Cleaning for oxygen service
	EA	Special calibration run
	NH	Customer specified ID
	NJ	CE approved
	PW	1/8 DIN digital indicator
	TH	Zero and span adjustment

Other options available upon request.

Note: Vented gage units should only be installed in environments that allow the breather to remain dry and free from contamination. Application of some available options may affect standard performance. Consult your Viatran Representative for details.



Information is accurate to the best of Viatran's knowledge. We reserve the right to change specifications at any time.
98PB120X48 11/2012

MECO MEASUREMENTS & CONTROLS
Via Paolo Uccello, 4 20148 Milano
Tel. +39 02 4 692 680 Fax +39 02 4 694 602 info@mecoitalia.it www.mecoitalia.it
Viatran A Dynisco Company